

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 6028 (2002): Green Bananas - Guide for Storage and Transport [FAD 10: Processed Fruits and Vegetable Products]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



भारतीय मानक
हरे केले — भंडारण एवं परिवहन हेतु निर्देशिका
(दूसरा पुनरीक्षण)

Indian Standard
GREEN BANANAS — GUIDE TO STORAGE
AND TRANSPORT
(*Second Revision*)

ICS 67.080.10

© BIS 2002

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

NATIONAL FOREWORD

This Indian Standard (Second Revision) which is identical with ISO 931 : 1980 'Green bananas — Guide to storage and transport' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on the recommendation of the Processed Fruits and Vegetables Sectional Committee and approval of the Food and Agriculture Division Council.

Banana is one of the most important food crops. Besides their large consumption within the country, bananas have been increasingly figuring in exports from India. Green bananas are required to be transported to long distances and for varying lengths of time before they are finally consumed. Therefore, in order to ensure that bananas reach the consumer's end in a proper condition, it is necessary that they are maintained under certain conditions so as to prolong their storage in an unripe condition. However, for this purpose, it is necessary that the bananas are harvested at a certain stage of maturity, are healthy, and also handled properly during different phases of transport and storage. This guide is issued with a view to assist those engaged in exporting bananas, in their scientific handling, transport and storage.

This standard was first published in 1971 and revised in 1983. In the first revision of this standard, considerable assistance was derived from ISO/R 931-1969 'Green bananas — Guide to storage and transport'. The second revision has been brought out to align it with the latest edition of the ISO Standard.

In the adopted standard, certain terminology and conventions are not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear referring to this standard, they should be read as 'Indian Standard'; and
- b) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a point (.) as the decimal marker.

In the preparation of this guide, due consideration has been given to the provisions of the *Cold Storage Order*. However, the provisions specified in the guide are subject to restrictions imposed under this Order.

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value, should be the same as that of the specified value in this standard.

Indian Standard
**GREEN BANANAS — GUIDE TO STORAGE
AND TRANSPORT**
(Second Revision)

0 Introduction

Bananas should be stored, before transport from the exporting country to the place of consumption and throughout the period of transport, in the green condition and, therefore in the preclimacteric phase.

A banana is said to be in the preclimacteric phase when the process of ripening has not yet been initiated.

Harvesting of bananas takes place throughout the year in tropical and sub-tropical regions having considerable variations of an ecological and climatic kind. It follows that the state of dimensional development (fullness) of the banana does not afford a precise criterion of its degree of ripeness. A thin banana (in a period of drought) may be in an advanced degree of ripeness.

Moreover, the degree of ripeness to be chosen depends on the duration of transport, which varies considerably (from a few days to 3 weeks).

The producer should time the cutting of the bananas so that the degree of ripeness (as estimated from their fullness) is compatible with the transport envisaged. The time of cutting, therefore depends on two distinct factors : the duration of refrigerated transport and the physiological state of the banana. For this reason the recommendations for the degree of ripeness (see 2.1) cannot be universally applicable and can be only of a general nature which serve as a pointer to the producer, who has to decide on his own criteria for cutting.

As regards examination for ripeness, a bunch of bananas may be likened to a bunch of grapes with fruit in different states of ripeness, and it is therefore essential to specify with what fruit the check is to be carried out.

The state of the bananas (state of health, wounds, etc.), when they enter the store, has an influence on the storage life, and this is the justification for making recommendations on this subject.

The same applies to the precautions to be taken between harvesting the bananas and putting them into the store. The high temperature of the producing areas and exposure to sunlight can appreciably reduce the storage life.

The term *cultivar* is used to indicate that the varieties of bananas entering into commerce are cultivated varieties.

Anti-fungal treatments of the ends of the main stalk or ends of

the cushions have not been mentioned, because it is not possible to indicate treatments which are recognized beyond dispute.

1 Scope and field of application

This International Standard describes conditions for the successful keeping, with or without artificial cooling, of green bananas, *Musa* sp., in the preclimacteric phase during storage before transport from the place of production to the place of consumption and during maritime transport.

2 Conditions of harvesting and putting into store

2.1 Harvesting

The degree of ripeness of the banana at harvesting should be determined as a function of its firmness and the number of days elapsing between harvesting and putting into the ripening room. It should not be too advanced, in order that the bananas may remain in the preclimacteric phase until they are put into the ripening room in normal conditions of transport.

2.1.1 Criteria of ripeness

The criteria of ripeness most generally used in practice are :

- the fullness, which is a dimensional criterion;
- the colour of the flesh, which is a criterion of the physiological state and is assessed by means of a conventional colour scale enabling a numerical value to be obtained;
- the firmness of the flesh, which is a criterion of the physiological state and is measured by means of a spring penetrometer (with a cylindrical end 4 mm in diameter, and a spring which is reduced in length by 100 mm under a force of 24,5 N);
- the characteristic odour of the flesh of the banana in the preclimacteric phase.

These criteria are not universally valid and, for each cultivar grown in the same way, they can vary from one region to another, and the producer should decide on his own criteria for cutting.

2.1.2 Examination for degree of ripeness

Examination for the degree of ripeness of a bunch of bananas should be carried out by using the representative fruit found in that part of the bunch which is in the most advanced state of ripeness, i.e. in the first or second hand reckoned from the largest end of the main stalk. The representative fruit is the centre fruit of normal shape in the inside row of the first or second hand. The degrees of ripeness of the fruits of the first and second hand can be considered as equal.

2.2 Quality characteristics for storage and transport

The bananas should be free from signs of attack by fungi, bacteria, insects or animal pests, and should be free from parasites. They should not be injured by fungal or physiological diseases.

In order to avoid the development of fungal diseases during storage, the fruit should be clean. It should not be stained with sap and the fruit stalks should be intact. The main stalk of the bunches should not show marks of sunburn and its two sections should be fresh, clean, and without smears, tears or breaks.

The bananas should be free from evident marks of rubbing, scraping, bruising or sunburn.

Removal of the pistils should be carried out in those producing areas where the climate and conditions of cultivation favour the development of rot. It should be carried out on the tree itself if the size of the banana tree allows this.

2.3 Putting into store

The bananas should be put into cold store for long journeys, or into ventilated store for short journeys, as soon as possible after harvesting. The interval between cutting the bunch and putting it into a refrigerated or ventilated enclosure (pre-refrigeration room, storage room or ship's hold) should be less than 24 h if possible, and should not in any case exceed 48 h.

After harvesting and packaging, if the bananas are awaiting land transport to the port of embarkation, they should be put in the shade and in a well ventilated place.

At the port of embarkation, the waiting time of lorries or wagons loaded with bananas, before transfer to the ship's holds, should be reduced to the minimum and the vehicles should be in the shade.

2.4 Method of storage

Green bananas should be stored :

- in hands or portions of hands (clusters) in cartons;

- in bunches, in bags of perforated polyethylene;

- in bunches, enclosed in a protective mattress which allows gas exchange and has a thermal conductance sufficient to ensure satisfactory cooling (straw, paper, etc.);

- in uncovered bunches, arranged in bulk. This method of storage should be carried out with very great care in order to avoid damaging the bananas, which would lead to deterioration during transport and ripening.

3 Optimum storage and transport conditions (with artificial cooling)

Refrigerated storage and transport of green bananas comprises two phases : cooling and storage.

3.1 Cooling

3.1.1 Rate of cooling

Cooling of the bananas should be carried out as rapidly as possible. It depends on the following factors :

- the power of the refrigeration plant (of the order of 700 to 800 calories per hour per tonne of bananas). With a central refrigeration plant, and loading of the banana vessel divided between two days, it is possible to apply the whole of the refrigerating power of the vessel to the first half of the cargo from the start of refrigeration and to dispose of more than 1 000 calories per hour per tonne of bananas;
- the air circulation ratio¹⁾ in each ventilation section;
- the uniformity and speed of the air circulation across the load;
- the surface of each package in contact with the cooling air;
- the efficiency of ventilation (effect of external and internal short-circuits of the air);
- the mode of packaging (polyethylene wrappers or cardboard boxes of different kinds);
- the method of storage (compact or in stacks);
- the method of loading the banana vessel (continuously or in 2 days with an interval of 12 h at night).

1) *Air-circulation ratio* is defined as the ratio of the volume of air passed in 1 h by the fans to the volume of the empty chamber.

3.1.2 Temperature

The temperature of the bananas is lowered from 25 to 30 °C, which is that of the bananas on loading into the ship's holds, to the practical storage temperature (see 3.2.1).

3.1.3 Relative humidity

The relative humidity of the air at the delivery side varies whilst the bananas are being cooled because the working range of the cold batteries is not stable. It increases at the end of cooling, when it should lie between 85 and 90 % at the entry of the delivered air into the banana compartments.

3.1.4 Air circulation

An *air circulation ratio* of 80 to 100 per ventilation section (collection of compartments, usually two, depending on the same fan or fans) is recommended.

The ventilation system recommended is that with vertically ascending or descending air in series (two compartments superimposed and separate by a slatted floor), with a uniform distribution of air over the surface at the suction side or the delivery side. Each compartment is traversed by all the air delivered by the fans and consequently its air circulation coefficient is double that of the ventilation section.

The rate of air change¹⁾ recommended is one change per hour, but it may be reduced to half a change per hour during cooling in order not to retard this.

3.2 Storage

3.2.1 Temperature

Throughout the period of maritime transport, after cooling of the bananas, it is necessary to ensure that the practical storage temperature of the delivery air is maintained at the value adopted. This is achieved by adding to the critical storage temperature (the temperature which induces damage to the bananas due to cold) a safety margin sufficient to take account of unavoidable temperature fluctuations arising from the refrigeration plant and its operation (+ 0,2 to + 0,5 °C for a refrigeration plant using brine; + 0,5 to + 0,7 °C for a direct expansion plant).

The critical temperature for bananas is not constant, its value depending on the cultivar considered, on the degree of maturity of the crop, its sanitary state, and the duration of the maritime transport.

The following values are given as indications only :

Cultivar	Period of storage days	Critical temperature ²⁾ °C
Gros Michel	12	12
Lacatan	11 to 13	14,4
Poyo (Robusta)	14	12
Grande naine		
(Giant Governor)	14	12
Petite naine		
(Dwarf Cavendish)	16	12

3.2.2 Relative humidity

The surface of the air coolers should be designed so that a relative humidity of 85 to 90 % is obtained at the cold point of the refrigerated enclosure in the stabilization period when the cooling of the bananas is completed.

3.2.3 Air circulation

During storage, the air circulation ratio may be reduced to half after the end of the cooling period.

The recommended rate of air change is one change per hour.

3.2.4 Ripening

Ripening of the bananas during storage should be avoided by all possible means. Ripening is accompanied by an increase in the production of carbon dioxide and by the production of ethylene, which is liable to trigger the ripening of the adjacent bananas.

Experience in storage shows that with an efficient ventilation system, ensuring continuous sweeping of all parts of the load by the air circulating in the holds of banana vessel, and with continuous changes of fresh air, carbon dioxide and ethylene can be removed without any action on the adjacent fruit.

The occurrence of an abnormal percentage of ripe bananas on discharge of the banana vessel arises from four causes which should be avoided :

- keeping at ambient temperature at the port of arrival;
- loading of bananas at too advanced a stage of ripeness;
- defects in ventilation;
- defects in the refrigeration plant.

1) The *rate of air change* is the ratio of the volume of outside air introduced into the refrigerated enclosure in 1 h to the volume of the empty enclosure.

2) *Critical temperature* is the temperature from or below which, for a given period of storage, physiological disorders are produced or it is not possible to obtain normal ripening when the product is taken out of storage.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc : No. FAD 10 (1008).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters :

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110 002
Telephones : 323 01 31, 323 33 75, 323 94 02

Telegrams : Manaksanstha
(Common to all offices)

Regional Offices :

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg
NEW DELHI 110 002

Telephone
{ 323 76 17
323 38 41

Eastern : 1/14 C.I.T. Scheme VII M, V. I. P. Road, Kankurgachi
KOLKATA 700 054

{ 337 84 99, 337 85 61
337 86 26, 337 91 20

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160 022

{ 60 38 43
60 20 25

Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600 113

{ 254 12 16, 254 14 42
254 25 19, 254 13 15

Western : Manakalaya, E9 MIDC, Marol, Andheri (East)
MUMBAI 400 093

{ 832 92 95, 832 78 58
832 78 91, 832 78 92

Branches : AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE.
FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.
LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM.